



MGSL-N Series

Electric Self-Propelled Scissor Lifts

STANDARD FEATURES

- MANUAL EMERGENCY LOWER SYSTEM
- PLATFORM SWING GATE
- EXTENDED PLATFORM
- FOLDABLE PLATFORM
- MULTI-DISC WET BRAKE
- MANUAL BRAKE RELEASE
- POTHOLE PROTECTION
- NON-MARKING TIRES
- AC POWER TO PLATFORM
- TILT ALARM
- BUZZER
- SAFETY BRACKETS
- CHARGING INDICATOR
- FORKLIFT POCKETS
- DIAGNOSIS SYSTEM
- MAINTENANCE FREE BATTERY
- DUAL FLASHING BEACON

OPTIONAL FEATURES

- AIRLINE TO PLATFORM
- POWER SOCKET TO PLATFORM
- PLATFORM WORKLIGHT
- OVERLOAD SENSOR
- HORN
- ANTI-COLLISION SYSTEM
- TOP LIMIT PROTECTION AUTO-STOP DEVICE
- MOTION ALARM

SPECIFICATION			
Model		MGSL-2265N	MGSL-2508N
Working Height Max.	H1	6.5m	7.8m
Platform Height Max.	H2	4.5m	5.8m
Platform Height Min.		0.93m	1.03m
Length - Platform Extension		0.9m	
Lifting Capacity		270kg	230kg
Lifting Capacity (On Extension)		115kg	
Platform Dimensions	B C A	1.64 x 0.75 x 1.1m	
Extended Platform Length	K	2.54m	
Platform Skirting Board Height	L	0.15m	
Overall Length & Width	E F	1.93 x 0.77m	
Height Stowed	D	2.04m	2.13m
Height - Guardrails Folded	M	1.69m	1.78m
Wheelbase	G	1.32m	
Ground Clearance	H	0.06m	
Ground Clearance - Deployed Potholes		0.02m	
Turning Radius - Inside		0.8m	
Turning Radius - Outside		1.56m	
Rising Time / Lowering Time		11s / 8.5s	14s / 11s
Drive Speed - Stowed		3.8km/h	
Drive Speed - Raised		0.7km/h	
Gradeability		30%	
Tilt Sensor - Front To Back		3°	
Tilt Sensor - Side To Side		2°	
Driving Motor Power		Hydraulic / Electric	
Hydraulic Tank Capacity		15L	
Tire Size		356 x 114 x 254m	
Max. Platform Occupancy		2 pers	
Power Source		4 x 6 V / 225Ah	
Weight - ANSI/CSA Standard		1164kg	1315kg
Weight - CE /AUS Standard		1235kg	1490kg

